MATERIAL SAFETY DATA SHEET

Date Prepared: 01/01/97

1. PRODUCT IDENTITY

Distributed by . . . INKADINKADO Inc.

Woburn, MA 01801 (617) 938-6100

If no enswer at phone number above, call 24 hour Emergency Phone: 800-468-6942.

II. HAZARDOUS INGREDIENTS

Following testing and formula evaluation, this product has been determined to be free of scute and chronic health hazards. This product and labeling conform to ASTM D4236.

III. PHYSICAL CHARACTERISTICS

Appearance . . , , . . Colored Liquid (paint) Odor Slight Odor of Ammonia

Solubility in Weter . . Dispersible Specific Gravity . . . Greater than 1

Ph 8.5

Top Five Ingredients . . Water, Waterbased Binder (Polymer Mixture), Pigment Dispersion, Pagricacent Powder, Textile

Softener

IV. FIRE & EXPLOSION DATA

Flash Point MA

Extinguishing Media . . Water, Dry Chemical, CO2, Foam

Fire Fighting Procedure: While no special procedures are required for

this product, firefighters should be equipped with self-contained breathing apparatus to protect egainst potentially toxic and

irritating fumes.

Explosion Hazards . . . None Likely

V. REACTIVITY DATA

Stability Stable

Polymerization Not Applicable

Incompatibility . . . Oxidizing and reducing agents

Hezerdous Decomposition Products: Burning may release CQ; CO2; HCN; oxides of sulfur, nitrogen, or titenium; or

other potentially toxic funes.

VI. HUNAN HEALTH DATA

When used in accordance with menufacturer's instructions in either home hobby or occupational setting, this product is believed to pose no scute or chronic health hezerds.

VII. EMERGENCY & FIRST AID PROCEDURES

induce vomiting.

Inhelation , Remove to fresh air. If breathing difficulty persists, call a physician.

This product is listed with POISINDEX(R) TOXICOLOGY INFORMATION SYSTEM.

Contact your local Poison Information Center for further help.

VIII. RECONNENDED HYGENIC PRACTICES

Whenever working with a special material such as this paint, users must take due precautions to protect their health. Avoid ingestion or eye contact. Avoid widespread prolonged skin contact. Wash hands before eating. Provide ventilation whenever spraying, and if painting or heatsetting this product for extended periods in a confined area.

1X. PERSONNEL PROTECTION RECOMMENDATIONS

Eye Protection None normally required. Wear protective goggles if use is likely to cause spattering of product in the direction of the eyes.

Skin Protection . . . None normally required, as minor short-term skin contact incidental to normal application should not be harmful. If use is likely to result in widespread prolonged skin contact, wear gloves and other protective clothing.

Ventilation If apraying this paint, use local ventilation or a NIOSH-approved mask (for particulates) to avoid inhelation of paint mists. Previde ventilation if heatsetting in a confined area.

X. SPILL OR LEAK PROCEDURES

Spills should be confined and liquid taken up with absorbent materials and placed in containers for proper disposal.

Waste Disposal Method . Small consumer quantities may be poured out onto paper, ellowed to dry, and disposed of with normal solid waste. Industrial quantities must be disposed of in accordance with existing federal, state and local environmental laws.

This information is based on data provided by our suppliers, and is accurate to the best of our current knowledge. The user hust judge the

This information is based on data provided by our suppliers, and is accurate to the best of our current knowledge. The user must judge the suitability of this information for any particular purpose. No other warranty is given.